

DRIVER DETAILS

NAME	COLIN PRICE
DATE	MARCH 2016
EVENT	COTSWOLDS TEST
WEATHER	DRY
RESULT	N/A
FASTEST LAP TIME	N/A

NOTES

26° INSIDE WHEEL LOCK



mi6 racing intelligence



CHASSIS AND ELECTRICS

CHASSIS	Alloy <input type="checkbox"/>	Carbon <input checked="" type="checkbox"/>		
TOP DECK	2.0mm <input checked="" type="checkbox"/>	2.5mm <input type="checkbox"/>	3.0mm <input type="checkbox"/>	4.0mm <input type="checkbox"/>
BODYSHELL	NAZDA 3			
WING	SCHUMACHER			
E.S.C	HW			
SERVO	KO			
RECEIVER	SANWA			
CELLS	INTELLECT 6000			

MOTOR AND GEARING

MOTOR	HW 4.5
ROTOR DIAMETER	STD
TIMING	STD
GEAR PITCH	48DP <input checked="" type="checkbox"/> 64DP <input type="checkbox"/>
SPUR SIZE	84T
PINION SIZE	22T

TRACK CONDITIONS

GRIP LEVEL	High <input type="checkbox"/>	Medium <input checked="" type="checkbox"/>	Low <input type="checkbox"/>
TYPE	Tight <input type="checkbox"/>	Open <input checked="" type="checkbox"/>	Mixed <input type="checkbox"/>
SURFACE	Carpet <input type="checkbox"/>	Tarmac <input checked="" type="checkbox"/>	
CONDITION	Smooth <input type="checkbox"/>	Bumpy <input checked="" type="checkbox"/>	
TEMPERATURE	10 °C		°F
VENUE	Indoor <input type="checkbox"/>	Outdoor <input checked="" type="checkbox"/>	

WHEELS, TYRES AND INSERTS

WHEELS	SOREX XG-32RY
TYRES	PRE-GLUED
INSERTS	PRE-GLUED
TYRE ADDITIVE	MR 33
ADDITIVE TIME	Front 15 Minutes Rear 15 Minutes
TYRE WARMERS	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Temp 60 °C Time 15 Minutes

FRONT

Spool
Gear Diff

Diff Oil N/A cTs

1 Dot - 1.1mm
2 Dot - 1.2mm
3 Dot - 1.3mm
4 Dot - 1.4mm
5 Dot - 1.5mm

Line In
Line Out

Shims 0mm

Droop..... 5.0 mm
On 10mm Block
Ride Height 5.8mm
Camber..... -1.5 °
Toe..... 0.5 °
Pivot Block Strap

Washers 1.0mm

43.5 44.2 46.0

Washers 0.5mm
Washers..... 0mm

Washers 0mm

Washers 1.5mm

12mm
13mm
14mm

4° R
4° Yoke
6° Yoke

SERVO SAVER Yes
No

Alloy Steel Double Joint

Narrow
Medium (kit)

Washers 1.0mm

Cap Type Vented Sealed Emulsion

Oil..... 450 cTs

Spring..... GREEN

Piston..... STD

Drilled Yes No

Drilled piston Hole Size..... 1.1mm

Shock Length (X)..... STDmm

Rebound 25%

Peripheral Damping Yes
No

REAR

Diff Oil 1000 cTs

0 Dot - 1.0mm
1 Dot - 1.1mm
2 Dot - 1.2mm
3 Dot - 1.3mm
4 Dot - 1.4mm

Medium
Wide (kit)

Droop..... 4.0 mm
On 10mm Block
Ride Height 6.0mm
Camber..... 2.0 °
Pivot Block Strap

Washers 0.5mm

44.2 45.5 46.1

Washers 1.0mm

WheelBase Short
 Middle Long

Alloy Steel

Shims..... 0.5mm

Shims 0.5mm

Cap Type Vented Sealed Emulsion

Oil..... 450 cTs

Spring..... GREEN

Piston..... STD

Drilled Yes No

Drilled piston Hole Size..... 1.1mm

Shock Length (X)..... STDmm

Rebound 25%

Peripheral Damping Yes
No