

DRIVER DETAILS

NAME	ELLIOT HARPER
DATE	FEB 2016
EVENT	MARITIME TEST
WEATHER	N/A
RESULT	N/A
FASTEST LAP TIME	N/A

NOTES



CHASSIS AND ELECTRICS

CHASSIS	Alloy <input type="checkbox"/>	Carbon <input checked="" type="checkbox"/>		
TOP DECK	2.0mm <input type="checkbox"/>	2.5mm <input checked="" type="checkbox"/>	3.0mm <input type="checkbox"/>	4.0mm <input type="checkbox"/>
BODYSHELL	MAZDA 6			
WING	SCHUMACHER BLACK			
E.S.C	LRP			
SERVO	SANWA			
RECEIVER	SANWA			
CELLS	LRP			

MOTOR AND GEARING

MOTOR	LRP 4.5	
ROTOR DIAMETER	STD	
TIMING	STD	
GEAR PITCH	48DP <input type="checkbox"/>	64DP <input checked="" type="checkbox"/>
SPUR SIZE	118T	
PINION SIZE	29T	

TRACK CONDITIONS

GRIP LEVEL	High <input type="checkbox"/>	Medium <input checked="" type="checkbox"/>	Low <input type="checkbox"/>
TYPE	Tight <input type="checkbox"/>	Open <input type="checkbox"/>	Mixed <input checked="" type="checkbox"/>
SURFACE	Carpet <input checked="" type="checkbox"/>	Tarmac <input type="checkbox"/>	
CONDITION	Smooth <input checked="" type="checkbox"/>	Bumpy <input type="checkbox"/>	
TEMPERATURE		5 °C	°F
VENUE	Indoor <input checked="" type="checkbox"/>	Outdoor <input type="checkbox"/>	

WHEELS, TYRES AND INSERTS

WHEELS	SOREX XG-32RK				
TYRES	PRE-GLUED				
INSERTS	PRE-GLUED				
TYRE ADDITIVE	NOSRAM CARPET				
ADDITIVE TIME	Front 10 Minutes	Rear 10 Minutes			
TYRE WARMERS	Yes <input type="checkbox"/>	No <input checked="" type="checkbox"/>	Temp °C	Time	Minutes

FRONT

Spool
Gear Diff
Diff Oil N/A cTs

1 Dot - 1.1mm
2 Dot - 1.2mm
3 Dot - 1.3mm
4 Dot - 1.4mm
5 Dot - 1.5mm

Droop..... 5.6 mm
On 10mm Block
Ride Height 5.2 mm
Camber..... -1.5 °
Toe..... 1.0 °
Pivot Block Strap
43.5 □ 44.2 □ 46.0 □

Washers 0 mm

Line In
Line Out

Shims 0 mm

Washers 0.5 mm
Washers 0 mm

Washers 1.5 mm

12mm
13mm
14mm

Cap Type Vented Sealed Emulsion
Oil..... 450 cTs
Spring..... BLUE
Piston..... STD
Drilled Yes No
Drilled piston Hole Size..... 1.1 mm
Shock Length (X)..... STD mm
Rebound 0 %

Peripheral Damping Yes No

4° R 4° Yoke
6° Yoke
SERVO SAVER Yes No

Alloy Steel Double Joint

Narrow Medium (kit)

Washers 1.0 mm

REAR

Diff Oil 1300 cTs

1.0 mm 1.0 mm

Medium Wide (kit)

Droop..... 4.0 mm
On 10mm Block
Ride Height 5.4 mm
Camber..... 2.0 °
Pivot Block Strap

Line In
Line Out

Washers 0.5 mm

Shims 0 mm

0 Dot - 1.0mm
1 Dot - 1.1mm
2 Dot - 1.2mm
3 Dot - 1.3mm
4 Dot - 1.4mm

(2 Pip shown)
0 Groove
1 Groove
2 Groove

Washers 1.0 mm

WheelBase Short Middle Long

Washers 1.0 mm

Alloy Steel

Cap Type Vented Sealed Emulsion
Oil..... 450 cTs
Spring..... WHITE
Piston..... STD
Drilled Yes No
Drilled piston Hole Size..... 1.1 mm
Shock Length (X)..... STD mm
Rebound 0 %

Peripheral Damping Yes No